

# VERUS

250 360



HORIZONTAL MILLING MACHINE

## TECHNICAL DATA

# VERUS

Corse - Travels - Verfahrwege - Courses		VERUS 250	VERUS 360
Longitudinale - Longitudinal - Längs - Longitudinale	mm (in)	4.000 - 20.000 (157,5 - 787,4)	4.000 - 20.000 (157,5 - 787,4)
Corsa Trasversale - Cross travel - Quer - Transversale	mm (in)	1.250 - 1.500 (49,2 - 59,0)	1.600 (63)
Corsa Verticale - Vertical travel - Vertikal - Verticale	mm (in)	2.000 - 2.500 (78,7 - 98,5)	3.100 - 3.600 (122 - 141,7)
Velocità di avanzamento - Feed rate - Vorschubgeschwindigkeit - Vitesse d'avance	mm/min (ipm)	35.000 (1.378)	30.000 (1.181)

### Elettromandrino - High-frequency spindle - Hochfrequenzspindel - Electrobroche

Potenza (S1) - Power (S1) - Leistung des Motors (S1) - Puissance (S1)	kW (Hp)	34 (45,5)	34 (45,5)
Coppia massima mandrino (S1) - Torque - Max. Spindeldrehmoment - Couple max.	Nm (lbf.ft)	830 (612)	830 (612)
Velocità massima di rotazione - Max. spindle speed - Maximale Drehzahl - Maxi vitesse de rotation	r.p.m	5.000 - 22.000	5.000 - 22.000
Attacco utensile - Spindle taper - Spindelkonus - Cône de broche		ISO 50 - HSK A63 - HSK A100	ISO 50 - HSK A63 - HSK A100

### Automatic Tool Changer

Utensili - Tools - Werkzeuge - Outils		N	40 - 80 >
---------------------------------------	--	---	-----------

