

RONIN EVO



HORIZONTAL MILLING
MACHINE

TECHNICAL DATA

RONIN EVO

Corse - Travels - Verfahrwege - Courses

Longitudinale - Longitudinal - Längs - Longitudinale	mm (in)	4.000 - 20.000 (157,5 - 787,4)
Corsa Trasversale - Cross travel - Quer - Transversale	mm (in)	1.250 - 1.500 (49,2 - 59,0)
Corsa Verticale - Vertical travel - Vertikal - Verticale	mm (in)	2.500 - 3.000 (98,4 - 118,1)
Velocità di avanzamento - Feed rate - Vorschubgeschwindigkeit - Vitesse d'avance	mm/min (ipm)	35.000 (1.377,9)
Spinta di lavoro asse - Axis work force - Achsvorschubkraft - Effort de travail d'un axe	X,Y,Z DaN (lbf)	2.200 (4.946)

Elettromandrino - High-frequency spindle - Hochfrequenzspindel - Electrobroche

Potenza (S1) - Power (S1) - Leistung des Motors (S1) - Puissance (S1)	kW (Hp)	up to 42 (56,3)
Coppia massima mandrino (S1) - Torque - Max. Spindeldrehmoment - Couple max.	Nm (lbf.ft)	up to 1.180 (870,3)
Velocità massima di rotazione - Max. spindle speed - Maximale Drehzahl - Maxi vitesse de rotation	r.p.m	5.000 - 18.000

Automatic Tool Changer

Utensili - Tools - Werkzeuge - Outils	N	40 - 80 - 120 →
---------------------------------------	---	-----------------

